



PERE-80 PERE-120 PERE-150

All dimensions shown are in millimetres

All stainless steel construction: **dia 32mm x 1mm tubes**
dia 38mm x 1.5mm headers

Connections: **1.2m long flying lead (3 core)**

Immersion heater rating: **IPX4**

Model	Output Watts	Weight kg	Height ± 2mm	Length ± 2mm	Fixing Centres ± 5mm
PERE-80-50/F	150	8	800	500	600
PERE-120-50/F	200	12	1200	500	1000
PERE-150-50/F	250	15	1500	500	1300

Tools & Material Required

Tape measure
 Screwdriver - crosshead
 Screwdriver - flathead
 Electric drill
 Masonry drill bit - 8mm diameter
 Spirit level
 Stepladder (for taller radiators)

Key	Component	Qty
A	Wall Plug	4
B	Bracket	4
C	Screw - Rnd Head, 6mm dia x 50mm	4
D	Grub Screw	4
E	Allen Key	1

Assembly Instructions

Accurately mark out bracket holes on wall using spirit level.

Drill four 8mm diameter holes to a minimum depth of 60mm & insert wall plugs (A).

Screw brackets (B) into wall plugs (A) with 6mm diameter x 50mm screws (C).

Slide boss on radiator into bracket (B) and secure in position by tightening grub screw (D) with allen key (E).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

