



Weights & n-coefficients

| Model | Weight (kg) | n-Coefficient | |
|-------|----------------|---------------|--|
| VR1/4 | 15.60 | 1.224 | |
| VR1 | 21.30 | 1.224 | |
| VR2 | 24.40 | 1.224 | |
| VR3 | 27.00 | 1.224 | |

Dual fuel heater kits

| Model | Dual Fuel Order Code | | | |
|---------|----------------------|--|--|--|
| VR1/4 | PTC300 | | | |
| VR1 | PTC400 | | | |
| VR2/VR3 | PTC500 | | | |

General specification



CERTIFICATION

Manufactured and tested to EN 442. Carries the CE Mark. Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - OHSAS 18001.



GUARANTEE

10 year guarantee from date of purchase against manufacturing defects.



COLOUR

Frame finished in chrome. Radiator in white (RAL 9016).



MATERIA

Frame manufactured from brass. Radiator manufactured from steel.



ACCESSORIES

Please see page 138.



SYSTEM

2 pipe pumped indirect domestic and commercial heating applications.



CONNECTIONS

 $2\,x\,{}^{1\!\!}/_{\!2}"$ BSP as standard.



AIR VENTS

Integrated.



OPERATING PRESSURES

Tested to a pressure of 9.6 bar. Working pressure of up to 7.4 bar.



UAL FUEL

PTC dual fuel heater kit options available. Please see table above or page 138.



APM° TECHNOLOGY

PTC heater kit comes with APM° technology. Please see page 261.



DELIVERY

2 - 5 working days.



VALVES

Please see page 138.

For more general information, please see page 260.

Technical information & heat outputs

| Order Code Nominal Height (H) (mm) | | Nominal Length (L) (mm) | Heat Outputs @ ∆T 50°C | | Heat Outputs @ ∆T 30°C | | Dual Fuel Rating |
|------------------------------------|-----|----------------------------|------------------------|-------|------------------------|-------|---------------------|
| | () | Watts | Btu/h | Watts | Btu/h | Watts | |
| VR1/4 | 955 | 476 | 423 | 1443 | 226 | 771 | 300 |
| VR1 | 955 | 676 | 602 | 2054 | 322 | 1099 | 400 |
| VR2 | 955 | 776 | 692 | 2361 | 370 | 1262 | 500 |
| VR3 | 955 | 876 | 783 | 2672 | 419 | 1430 | 500 |