



INTERLUDE

INTERLUDE is a simple and elegant flat tube radiator. It is manufactured from quality steel and has a sleek and streamlined appearance. It is both practical and attractive and is available in selected RAL, metallic or special metallic finishes.



RAL 9016
Traffic White

General specification



CERTIFICATION
Manufactured and tested to EN 442. Carries the CE Mark. Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - OHSAS 18001.



GUARANTEE
10 year guarantee from date of purchase against manufacturing defects.



COLOUR
Finished in white (RAL 9016) or selected RAL, textured, metallic or shimmer metallic colours. Please see page 262.



MATERIAL
Manufactured from steel.



SYSTEM
2 pipe pumped indirect domestic and commercial heating applications.



CONNECTIONS
2 x 1/2" BSP as standard.



AIR VENTS
Included in the packaging.



OPERATING PRESSURES
Tested to a pressure of 5.2 bar. Working pressure of up to 4 bar.



DUAL FUEL
ECO450 dual fuel heater kit available for INT2 & INT3 only. Please see page 138.




DELIVERY
Stocked items (white/RAL 9006): 2 - 5 working days. Non-stocked items (colour): 4 - 6 weeks.



VALVES
Please see page 138.

For more general information, please see page 260.

Dimensions



Weights, water contents & n-coefficients

Model	Weight (kg)	Water Content (l)	n-Coefficient
INT1	9.31	2.9	1.190
INT2	13.68	4.8	1.205
INT3	19.86	8.6	1.227

Technical information & heat outputs

Order Code	Nominal Height (H) (mm)	Nominal Length (L) (mm)	Heat Outputs @ ΔT 50°C		Heat Outputs @ ΔT 30°C		Dual Fuel Rating
			Watts	Btu/h	Watts	Btu/h	
INT1	530	500	295	1007	161	549	-
INT2	905	500	470	1604	254	867	450
INT3	1655	500	817	2788	435	1484	450