



Mounting Foot Detail

All dimensions shown are in millimetres

All steel construction:

Connections: **1.2m long flying lead (class II)**

Immersion heater rating: **IPX4 or better**

This radiator may only be installed horizontally on floor

| Model | Height ± 2mm | Width ± 2mm | Finish | Output Watts | Weight kg |
|-----------------|-----------------|----------------|---------|-----------------|--------------|
| FFZ-190-100/AF | 190 | 1000 | painted | 500 | 13.5 |
| FFZ-190-150/AF | 190 | 1500 | painted | 600 | 20.4 |
| FFZ-190-200/AF | 190 | 2000 | painted | 1000 | 27.3 |
| FFZC-190-100/AF | 190 | 1000 | chrome | 400 | 13.5 |
| FFZC-190-150/AF | 190 | 1500 | chrome | 500 | 20.4 |
| FFZC-190-200/AF | 190 | 2000 | chrome | 750 | 27.3 |

Issue 1.0



Tools & Material Required

Screws - 4mm diameter x 60mm length
Tape measure
Screwdriver
Electric drill
Masonry drill bit

| Key | Component | Qty |
|-----|------------------------|-----|
| A | Screw, 4mm dia x 60mm* | 4 |

* Screws not supplied

Assembly Instructions

Accurately mark out holes for mounting feet on floor to dimensions as shown on Technical Data Sheet.

Drill four holes to suit screws (A).

Fix radiator to floor with screws (A).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

