

Mounting positions, dimensions & wall brackets Safety Clip-on Brackets 300mm Wall Bracket 81 99 , () . 115 Height 500mm Wall Bracket Step 2 Step 1 8 236 100 Min Radiator to be hung on the short leg of the bracket. NB: All measurements are nominal.

General specification



CERTIFICATION

Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - ISO 45001:2018. Carries the CE mark and conforms to the Low Voltage Directive 2014/35/EU and the EMC Directive 2014/30/EU.



GUARANTEE

2 year guarantee from date of purchase against manufacturing defects.



COLOUR

Finished in white (RAL 9016).



MATERIAL

Manufactured from steel and filled with environmentally friendly vegetable oil.



ACCESSORIES

TOUCH4 - 4 zone touch screen programmer. Please see page 255.



SEALED ELECTRIC



IP RATED IP44.



DELIVERY 2 - 5 working days.



WASTE DISPOSAL

According to The WEEE Directive (2012/19/EU). Please see page 261.



ECO DESIGN DIRECTIVE

Conforms to the standards (EU) 2015/1188.

For more general information, please see page 260.

Technical characteristics

Measured temperature precision	0.1°C
Operating temperature	-10°C + 50°C
Setting temperature range	+5°C + 30°C
Control characteristics	PWM
Electrical protection	Class 1 – IP44
Power supply 230 VAC - 50 Hz	

For more information, please refer to the installation instructions available on our website.

Accessories

Product	Order Code
TOUCH4* - 4 Zone, Touch Screen Programmer (hard wired)	TOUCH4 - refer to page 255

^{*}Please refer to our website for wiring diagram.



TOUCH4*

Technical information & heat outputs

Order Code	Nominal Height (mm)	Nominal Length (mm)	Weight (packed - kg)	Rated Watts
FE30DX50	300	500	10.5	500
FE30DX80	300	800	16.5	750
FE30DX100	300	1000	20.5	1000
FE30DX130	300	1300	25.5	1250
FE30DX160	300	1600	31.5	1500
FE30DX200	300	2000	38.5	2000
FE50DX40	500	400	14.0	500
FE50DX50	500	500	17.0	750
FE50DX65	500	650	21.5	1000
FE50DX80	500	800	25.5	1250
FE50DX95	500	950	29.5	1500
FE50DX125	500	1250	39.1	2000