

Zehnder Roda

Hydronic operation

Product data sheet



Ideal for entrance halls, kitchens and bathrooms. Zehnder Roda takes up hardly any room. Actually it creates space! Useful accessories, such as hooks and towel rails, make the radiator Zehnder Roda even more practical. Available in all colours and surfaces from the Zehnder colour chart.

- Wide range of elegant accessories for a variety of combination options
- Wide range of models supports versatile use
- Short response time means rooms can be heated up rapidly
- High thermal output means large rooms are heated up rapidly

Horizontal models

With horizontal elements

Model	H mm	L mm	N	Heat output			
				75/65/20 °C	70/55/24 °C	55/45/24 °C	55/45/20 °C
				Watts	Watts	Watts	Watts
ROH-059-060	592	600	532	399	286	173	208
ROH-059-160	592	1600	1532	1064	762	462	554

H = height, L = length

75/65/20 = Nominal heat output according to EN 442

Horizontal models

With vertical elements

Model	H mm	L mm	Heat output			
			75/65/20 °C	70/55/24 °C	55/45/24 °C	55/45/20 °C
			Watts	Watts	Watts	Watts
ROHD30	296	1000	591	425	259	310
ROHD37	370	1000	715	514	314	376
ROHD44	444	1000	835	601	366	439
ROHD52	518	1000	953	686	418	501
ROHD60	592	1000	1069	769	469	562
ROHD67	666	1000	1183	851	519	622
ROHD74	740	1000	1295	932	568	680
ROHD-059-140	592	1400	1497	1076	656	786
ROHD-059-160	592	1600	1710	1230	749	897

H = height, L = length

75/65/20 = Nominal heat output according to EN 442

Vertical models

Model	H mm	L mm	Heat output			
			75/65/20 °C	70/55/24 °C	55/45/24 °C	55/45/20 °C
			Watts	Watts	Watts	Watts
ROV180	1800	74	142	101	60	72.7

H = height, L = length

75/65/20 = Nominal heat output according to EN 442

Vertical models

Model	H mm	L mm	Heat output			
			75/65/20 °C	70/55/24 °C	55/45/24 °C	55/45/20 °C
			Watts	Watts	Watts	Watts
ROVD180	1800	74	206	146	87	105

H = height, L = length

75/65/20 = Nominal heat output according to EN 442