



All dimensions shown are in millimetres

All stainless steel construction: **30mm x 50mm x 1.2mm tubes**
30mm x 30mm x 1.2mm headers

Connections: **1.2m long flying lead (3 core)**
 Immersion heater rating: **IPX4**

Model	Output Watts	Weight kg	Height ± 2mm	Length ± 2mm	Fixing Centres ± 5mm
ALBE_-100-50	200	13	1000	500	760
ALBE_-140-50	250	18	1380	500	1140
ALBE_-180-50	300	22	1760	500	1520

Tools & Material Required

- Tape measure
- Screwdriver - crosshead
- Screwdriver - flathead
- Electric drill
- Masonry drill bit - 8mm diameter
- Spirit level
- Stepladder (for taller radiators)

Key	Component	Qty
A	Wall Plug	4
B	Bracket	4
C	Screw - Rnd Head, 6.3mm dia x 60mm	4
D	Grub Screw	4
E	Allen Key	1

Assembly Instructions

Accurately mark out bracket holes on wall using spirit level.

Drill four 8mm diameter holes to a minimum depth of 60mm & insert wall plugs (A).

Screw brackets (B) into wall plugs (A) with 6mm diameter x 50mm screws (C).

Slide boss on radiator into bracket (B) and secure in position by tightening grub screw (D) with allen key (E).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

