Zehnder

Aluminium Blitz Super








In stock items highlighted in black	Height mm	Width mm	Number of sections	Finish	Overall Projection mm	Output ΔT=50°C Watts/btu All outputs certified to EN 442	
Sehnder Blitz S	Super horizor	ntal					
BS350/100-6	395	480	6	white	130	546/1863	
BS350/100-8	395	640	8	white	130	728/2484	
BS350/100-10	395	800	10	white	130	910/3105	
BS350/100-12	395	960	12	white	130	1092/3726	
BS350/100-14	395	1120	14	white	130	1274/4347	
BS500/100-6	545	480	6	white	130	737/2516	
BS500/100-8	545	640	8	white	130	983/3354	
BS500/100-10	545	800	10	white	130	1229/4193	
BS500/100-12	545	960	12	white	130	1475/5032	
BS500/100-14	545	1120	14	white	130	1721/5871	
BS600/100-6	645	480	6	white	130	848/2895	
BS600/100-8	645	640	8	white	130	1131/3860	
BS600/100-10	645	800	10	white	130	1414/4824	
BS600/100-12	645	960	12	white	130	1697/5789	
BS600/100-14	645	1120	14	white	130	1980/6754	


Powder coated RAL9010 white. Colour finishes are not available. Width excludes air vent and bushes (Additional 24mm)

The Blitz Super is a high output, low water content, die-cast aluminium radiator, sectional in manufacture, supplied with a bracket pack comprising wall fixing brackets, plugs, bushes and an air vent.

Joining nipples, gaskets and an assembly tool must be purchased separately.

Accessories		
Model		
A36/6	Towel rail for 6 section Blitz Super. White RAL9010 (see below)	
905110	Aluminium assembly tool 300	
905120	Aluminium assembly tool 600	
905130	Aluminium assembly tool 900	
905140	Aluminium assembly tool 1200	
A2/1	1 inch steel joining nipple – for use with Blitz Super	
A10/1	Joining nipple gasket for joining the Blitz Super. White RAL 9010	
A11/1	Gasket for end plugs for Blitz Super - Green	
A81	Installation bush and bracket pack for Blitz Super	
A80	Service assembly kit for the Blitz Super radiator	





All dimensions in mm

*1/2" air vent

F = flow R = return H = heightW = width

Width excludes air vent

Zehnder recommends VALVE-SET-10-CR. For more information see page 108.

Connections: $4\times1/2$ ", suitable for bottom opposite ends (BOE), top bottom opposite ends (TBOE) or top bottom same end (TBSE).

Aluminium radiators give a fast response and comfortable heat with high thermal efficiency. Energy saving and easy to handle plus corrosion resistant, the **Blitz Super** is a modern radiator in every sense.

By **fondital**



