



All dimensions shown are in millimetres

All steel construction: **70mm x 39mm triangular tube frame**  
**70mm x 8mm flat tubes**

Connections: **1.2m long flying lead (2 core)**

\* Radio Frequency Remote Programmer IPX4-1K09

Model	Height ± 2mm	Width ± 2mm	Finish	Electric Rating* Watts	Weight kg
METE-080-040/GF	805	400	painted	300	9.4
METE-120-040/GF	1225	400	painted	500	13.8
METE-120-050/GF	1225	500	painted	500	16.0
METE-120-060/GF	1225	600	painted	600	18.3
METE-150-050/GF	1540	500	painted	600	18.5
METE-150-060/GF	1540	600	painted	750	21.1
METE-180-050/GF	1750	500	painted	750	22.4

Issue 1.0



## Tools & Material Required

Tape measure  
Screwdriver - crosshead  
Pliers  
Electric drill  
Masonry drill bit  
Spirit level  
Stepladder (for taller radiators)

Key	Component	Qty
A	Boss	4
B	Wall Plug	4
C	Bracket	4
D	Screw, 6mm dia x 50mm	4
E	Washer	4
F	Grub Screw	4
G	Allen Key	1

## Assembly Instructions

- Screw bosses (A) to studs on the back of the radiator.
- Accurately mark out bracket holes on wall using spirit level.
- Drill four holes to a minimum depth of 65mm & insert wall plugs (B).
- Attach brackets (C) to wall with screws (D) & washers (E).
- Hang radiator onto wall by inserting bosses (A) into brackets (C).
- Tighten grub screws (F) with Allen key (G).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

*Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.*

